

EPOCH MASTER GLOBAL BUSINESS (JIANGSU) INC. RM.3-93, TENGFEI BUILDING, NO.88 JIANGMIAO RD., RESEARCH AND INNOVATION PARK, NANJING ZONE, (JIANGSU) PILOT FREE TRADE ZONE, CHINA

Calcium Silicate

General Characteristics:

Formula:	CaSiO ₃	
Molecular weight: 116.16		
Appearance:	Calcium silicate occurs as a white to off white, free-flowing powder that remains so after absorbing relatively large amounts of water or other liquids.	
Odor: CAS Number:	Odorless [1344-95-2]	
EINECS No.:	215-710-8	
INS:	552	
Solubility:	Insoluble in water, alcohol and alkali; soluble in strong acids.	
TT		

Uses:

- > Anticaking agent; filter aid.
- > Candy polishing agent; Yeast sugar powder.
- > Rice coating agent; deflocculant.

Packing and Storage:

- > 25kg net paper bag and PE bags sealed inside.
- Store in a well-closed bag at room temperature, protect from light, moisture and pest infestation.
- Shelf life--- two years

GMO-Status:

The product is a non GMO product and is free from any recombinant DNA.

Irradiation/Radioactivity:

Yunbo's Calcium silicate was never subjected to any kind of ionized irradiation and contains no radioactivity not even in minor amounts.

BSE/TSE:

No raw materials from bovine origin are used nor are any bovine constituents present in the product.



Specifications: (FCC/E552)

Test Parameter	Specification
Assay(SiO ₂)	50.0%~95.0
CaO	3.0%~35.0%
Test for silicate	Passes test
Test for calcium	Passes test
Lead	≤5.0ppm
Loss on Drying	≤10.0 % (105 °C, 2 hours)
Loss on Ignition	5 % ~14 % (1 000 °C, constant weight)
Sodium	≤3.0 %
Fluoride	≤10.0ppm
Arsenic	≤3.0ppm
Lead	≤2.0ppm
Mercury	≤1.0ppm

